



BLOCK-LINER

BL650

PRODUCT DESCRIPTION

ULTRATAP Block Liner, is a latex coated, non-woven fiberglass substrate for walls and ceilings. It is applied like a conventional wall-covering and can be used as a bridging material under wallcoverings, knockdown texture, or as a paintable surface.

ULTRATAP covers block, tile, knockdown texture, plaster, cracks, paneling, brick, damaged drywall, or other problem surfaces. For renovation, it becomes an economical and time saving alternative to skim coating.

PRODUCT USES

Public housing, schools, dormitories, hotels, hospitals, offices, military facilities, government facilities, condos, apartments and residences.

ENVIRONMENTAL STATEMENT

ULTRATAP is environmentally responsible and is free from PVC, chlorine, and heavy metals.

TECHNICAL DATA

Size: Each roll measures 39" (1 meter) wide x 10.9 yards (10 meters) long and equiv to 107.6 sq.ft.

Thickness: 0.7mm.

Weight: 650 g/m² or 19.17 oz/sq.yd.

Material Properties: Latex coated, non-woven fiberglass ground. Non shrinking.

Fire Rating: ASTM E84 Class A

WALL SURFACE PREPARATION

All wall or ceiling surfaces to be covered should be free of dust, dirt, stains, oily coatings, existing wallcoverings, loose paint or other compounds preventing adhesive bond or impairing performance of installed materials. Wall substrates must be even, and true to plane for proper installation. When covering surfaces such as knockdown texture, plaster, cracks, paneling, brick, masonry, tile, or damaged drywall, minimal surface preparation may be required to determine amount of surface preparation, it is recommended to install 3 test strips. For masonry, brick, and tile, level any surface projections and mortar spatters by grinding or scraping and fill mortar joints when a sound surface is required. For paneling, assure joined panel edges are secure and even. Filling grooves is required if grooves exceed 1/8" in width. Avoid seaming at grooves on paneling, masonry or tile. A 4-inch vertical, smooth surface prep of Durabond 90 is recommended where material is butt joined or double cut on masonry and tile applications. Porous and non-porous surfaces should be primed with adhesive promoting R35 or equivalent primer/sizer. Allow primed surface to dry thoroughly.

INSTALLATION GUIDELINES

Pre-cut **ULTRATAP** in appropriate lengths allowing 2 to 4 inches for trimming. Recommended adhesives are heavy duty clay or vinyl to vinyl. Apply adhesive to the back of the material using a 3/4" to 1" nap roller or pull through a pasting machine with a spread rate of approximately 150 -180 sq.ft. per gallon. Apply **ULTRATAP** by pressing the material onto the wall surface using a plastic smoother tool to eliminate air pockets and secure **ULTRATAP** to wall surface assuring a tight bond. Material may be overlapped and double cut to assure a tight seam. **However, it is recommended to allow the adhesive to 'setup' and bond with the wall surface at least 20 - 30 minutes before cutting the seams to avoid open seams.** A butt-join application may be acceptable. Work from center of strip toward edges. Trim along top and bottom with a sharp, fresh blade. All subsequent strips should be installed one strip at a time as above.

As a wallcovering liner:

Allow the installed **ULTRATAP** to dry thoroughly at room temperature prior to priming. Prime the wall liner with a pre-wallcovering primer to provide for proper bond between **ULTRATAP**, adhesive and wallcovering, and allow to dry. Install wallcovering according to manufacturer's specifications and recommended adhesives.

As a paintable surface:

Follow above installation guidelines and utilize an overlap and double cut method for a tight seam. Once material is installed and adhesive is thoroughly dry, prime **ULTRATAP** with a latex bonding primer, allow to dry thoroughly, and apply 2 coats of specified top-coat paint finish for best results.

As a knock-down texture underlayment:

Follow above installation instructions and utilize an overlap and double cut for a tight seam. Once material is installed and adhesive is thoroughly dry, follow knock-down texture manufacturer's application procedures.

LIMITATION OF LIABILITY To the best of our knowledge the technical data contained herein are true and accurate at the date of issuance but are subject to change without prior notice. We make no other warranty or guarantee of any kind, expressed or implied, including merchantability and fitness for particular purpose. Liability, if any, is limited to replacement of defective Block-Liner. Labor or cost of labor and other consequential damages are hereby excluded.

1-800-888-2776

*Ultratap is a trademark of Sempatap
Distributed by Roos International, Ltd. Inc.*

www.roosintl.com

Revised 10/07