

Technical Characteristics

Composition	100 % coated glass fiber
Treated fabric weight (average value)	130 g/m ² = 3,83 oz/yards ² (± 8 %)
LOI	44%
Emission in indoor air	A+
Oekotex certificate standard 100	Class I
Fire resistance (ASTM E84)	Class A Fire rated

Recommendation for application

Quantity of glue	250 g/m ² = 10,55 oz/yards ²
Quantity of acrylic paint	200–300 g/m ² = 8,44–12,66 oz/yards ²

Dimensions & Packaging

Width (individual value)	100 cm = 39,37 inches (± 1 % or closed pattern repeat)
Roll length (individual value) (1)	50 m = 54,68 yards (± 1 %)
Paintable surface (2)	Outside
Roll packaging (2)	Plastic foil
Label on roll (2)	With installation instructions
# rolls / pallet	24
Storage conditions	Dry room, storing temperature from 14 °F to 122 °F. If product is not processed up to one week, it is not recommended to open a package or to remove a package from a roll.

Quality Control

Traceability (2)	Lot no. marked on the back side of the roll and on the small sticker on the roll
Defects marked by label (2)	Maximum 3 point defects / 50 m = 50,68 yards
Each defect is balanced by	Adding 50 cm = 19,69 inches / defect (2)
Product is carefully checked before leaving the factory but should also be checked just before applying. Any claim should be accompanied with roll sticker and a sample featuring the defect..	

General Description

Glass fibers made into a non-woven smooth substrate veil, and coated with the special antimicrobial coating. This pre-painted product saves one layer of paint during application and 1 day of paint drying time. Requires finish coat of paint after installation when adhesive thoroughly dry. Mold-X technology contributes to sanitary environment – no development of bacteria and mold on the surface even after several layers of paint. This Mold-X product still offers durable protection to walls and ceilings by reinforcing the surfaces; resisting abrasion; providing impact resistance, and covering cracks; and can easily be repainted when time to redecorate. Suitable for residential or commercial projects whether **new construction or renovation**.

(1) Other dimensions or features on request
(2) Details are described in works standard 0337

Properties

- Tear resistant
- Easy re-paintable
- Prepainted
- High tensile strength
- Breathable
- Absorbs formaldehyde
- Fire resistant
- Flat finish

