



TEXTURGLAS®

Technical Summary

Pattern No.	Weight oz./sq.yd.	Width & Length/meter Total Sq.Ft. +/-	Tensile Strength		Paint Consumption Primer and top coat (top coat only for pre-primed) sq. ft./gal/per coat apprx.
			lbs/in warp apprx.	lbs/in weft Apprx.	

Note: Below weaves require a primer coat and a finish coat of paint

Standard Weaves					
TG3	4.04	39.4" x 54.5 yds./538 sq.ft	160	90	220
TG4	3.92	39.4" x 54.5 yds./538 sq.ft	90	110	180
TG5	4.95	39.4" x 54.5 yds./538 sq.ft	80	110	180
TG7	5.46	39.4" x 54.5 yds./538 sq.ft	100	210	120
TG8	2.6	39.4" x 54.5 yds./538 sq.ft	90	60	180
TG11	6.03	39.4" x 54.5 yds./538 sq.ft	160	190	180
TG12	7.50	39.4" x 54.5 yds./538 sq.ft	130	230	120
TG15	5.22	39.4" x 54.5 yds./538 sq.ft	110	150	120
TG16	4.18	39.4" x 54.5 yds./538 sq.ft	150	140	120
TG17	5.42	39.4" x 54.5 yds./538 sq.ft	190	110	120
TG21	5.49	39.4" x 54.5 yds./538 sq.ft	90	170	120
TG51	5.46	39.4" x 54.5 yds./538 sq.ft	90	160	120
TG53	5.49	39.4" x 54.5 yds./538 sq.ft	90	160	120
TG54	4.95	39.4" x 54.5 yds./538 sq.ft	80	110	180
TG55	6.20	39.4" x 54.5 yds./538 sq.ft	130	90	120
TG56	5.37	39.4" x 54.5 yds./538 sq.ft	90	150	120
TG57	3.32	39.4" x 54.5 yds./538 sq.ft	70	80	180
TG61	5.04	39.4" x 54.5 yds./538 sq.ft	90	170	120
TG62	4.48	39.4" x 54.5 yds./538 sq.ft	110	150	120
TG63	5.57	39.4" x 54.5 yds./538 sq.ft	90	160	140

Note: Below weaves are pre-primed and require no primer coat and only one coat of finish paint in low lustre satin or eggshell, or 2 coats in dark colors.

Pre-primed Weaves					
TGP3	4.04	39.4" x 54.5 yds./538 sq.ft	160	90	300
TGP4	3.92	39.4" x 54.5 yds./538 sq.ft	90	110	280
TGP5	6.46	39.4" x 54.5 yds./538 sq.ft	90	140	200
TGP7	5.46	39.4" x 54.5 yds./538 sq.ft	100	210	180
TGP11	6.03	39.4" x 54.5 yds./538 sq.ft	160	200	280
TGP21	5.49	39.4" x 54.5 yds./538 sq.ft	90	170	180
TGP51	5.46	39.4" x 54.5 yds./538 sq.ft	90	160	180
TGP53	5.49	39.4" x 54.5 yds./538 sq.ft	90	160	180

Paint Consumption:

Amount is based on latex paint and is for basic guidelines only. Exact amounts will vary according to type and quality of paint and application technique. High quality paints and primers are recommended for the best results.

"TG" patterns requires a primer coat and a finish coat and takes approximately 3 - 4 gallons per 538 sq.ft. combined.

"TGP" patterns requires only one finish coat of low luster paint and takes approximately 2.5 - 3.5 gallons per 538 sq.ft.. Use a 3/4" to 1" nap roller.

Installation and adhesive:

Texturglas can either be installed utilizing a dry hang method, or may be pulled through a paste machine except for patterns TG3 and TGP3. When using a pasting machine, do not book the material -- take it directly to the wall. Do not use a seam roller. Use a good quality, heavy duty clear adhesive (do not dilute with water) for a strippable application, or a VOV for a non-strippable and wet room installation. Adhesive requirements are 3 to 4 gallons +/- per 538 sq.ft. approximately depending on pattern selection. For dry hang application, use a 3/4" to 1" nap roller.

Mildew Conditions:

Where mildew conditions exist, it is recommended that the wall surface be clean and free of mildew and stains prior to installation.

Replace gypsum with greenboard in areas where wallboard is saturated and deteriorated. Use primers, adhesives and paints with mildewcides such as Zinsser Company products. The Zinsser Plus system offers a 5 year mildew-proof primer/adhesive guarantee.

Permeability:

Texturglas is a permeable/breathable material even when painted with a latex paint. It has a significantly high perm rating that allows moisture to escape.

Fire Rating:

Texturglas is Class A fire rated according to ASTM E84-01/NFPA255. Flame spread: 15, Smoke Develop: 0

Environmental Issues:

Texturglas is made of all natural materials and is approved by OkoTex in Europe for no harmful substances. Texturglas is listed in GreenSpec® as a 'green' wallcovering because it does not contain PVC's and releases minimal pollutants. It qualifies for LEED credits: IEQ Credit: 3.

For additional information, contact Roos International, Ltd., Inc. at 1-800-888-2776 or website: www.texturglas.com