



INTERNATIONAL LTD. INC.

Architectural & Design Materials  
for a Healthier Building Environment

## ARCHITECTURAL SPECIFICATIONS

### RAINFOREST COLLECTION FLOATING RECYCLED LEATHER PLANKS AND TILES

#### **SPECIFICATIONS**

Style:	Floating Recycled Leather tiles a/o planks with cork backing
Description:	Recycled leather mounted on a formaldehyde-free high-density fiberboard backed cork with Uniclic® interlocking joint system
Thickness:	3/8"
Weight:	16 oz. per square foot
Nominal Sizes:	15 1/4" x 15 1/4" x 3/8" and 7 5/8" x 45 7/8" x 3/8"
Finish:	Water-based warranted floor protective finish (5 years commercial/ 25 residential)

#### **PERFORMANCE CHARACTERISTICS**

Taber Test (ASTM d 4060 – CS 17 wheel, 500 gr):	8,000 wear through cycles
Static Load Limit (ASTM F970):	005 inch
Slip Resistance (ASTM C1028):	Dry: 0.98 Wet: 0.98
Colorfastness (AATC- 100 hrs):	Class IV
Critical Radiant Flux (C –ASTM e 648):	0.41 (Class II)
Surface Burning Characteristics ( ASTM E-84):	Class C
FIIC Test (ASTM E989): <i>Test conducted over 8" concrete with no suspended ceiling</i>	59 (no underlay) 61 (with underlay)
Low-VOC (California standard Public School 01350):	Pass

#### **GREEN FEATURES**

Our recycled leather Floating Tiles may contribute to LEED for Commercial Interiors in:

MR:	4.1/ 4.2 Recycled Content (pre-consumer)
IAC:	4.2 / 4.3 Low-emission adhesive and product
Renewable:	6.0 Rapidly renewable resource and material

*EcoDomo LLC is a member of the US Green Building Council and CoopAmerica. We consider paying for carbon credits, wind-generated electricity, and recycled materials as essential as paying for rent and other utilities. Visit [www.EcoDomo.com](http://www.EcoDomo.com) for more details.*