



INTERNATIONAL LTD. INC.

Architectural & Design Materials
for a Healthier Building Environment

ARCHITECTURAL SPECIFICATIONS THE ECHELON COLLECTION RECYCLED LEATHER TILES

LEATHER SPECIFICATIONS

Style:	Recycled Leather Tiles (RLT)
Description:	Full-grain leather shredded bound with natural rubber and composites
Thickness:	1/8"
Weight:	9.5 per square feet (1/8")
Sizes:	4" x 4" up to 24" x 24"
Maximum Size:	57" x 39" x 1/8"
Finish:	Specialty finish designed for leather

PERFORMANCE CHARACTERISTICS

Wear Resistance - Frick-Taber Test (EN 660-2):	2.06 mg/100 revolutions
Abrasion Test ASTM D4060 (CS-17, 1 kg):	102 mg/1,000 cycles
Slip Resistance (SATRA TM 144):	Wet: 0.27 Dry: 0.76
Single-Flame Source Test (ISO 11925):	Pass
Flame Spread Test (ASTM E-84):	Class "C" standard Class "B" available as an upgrade
Breaking Force (ASTM D-2208):	600+ lbs
Elongation (ASTM D-2211) (psi):	0-50%
Static Load Limit (ASTM F-970) (100 lbs psi):	.0004 inch



GREEN FEATURES

VOC Emission (ISO 14814 - Water Method)

Class None as Detected (less than 20 mg/kg)

Natural and Rapidly Renewable Products

Leather, Latex, Acacia Tree Bark

Manufactured in the United States of America

500-mile radius

EcoDomo LLC is a member of the US Green Building Council. We consider paying for carbon credits, wind-generated electricity, and recycled materials as essential as paying for rent and other utilities. Visit www.EcoDomo.com for more details.