



ARCHITECTURAL SPECIFICATIONS ANDELINE RECYCLED LEATHER VENEERS

LEATHER SPECIFICATIONS

STYLE:	RECYCLED LEATHER VENEER & PANELS
DESCRIPTION:	COWHIDE LEATHER BOUND WITH NATURAL LATEX AND COMPOSITES
THICKNESS:	STANDARD : 1/64" - CUSTOM THICKNESSES AVAILABLE UP TO 1/16"
SIZES:	ROLLS : 57" x 100 YARDS SHEETS: 57" x 48" LAMINATED PANELS: 4'x 8' x 1/4" AND 4' x 4' x 1/4"
CUSTOM SIZES:	AVAILABLE IN TILES, SHEETS AND PANELIZED LEATHERS
FINISH:	SPECIALTY WATER-BASED ACRYLIC DURABLE FINISH

PERFORMANCE CHARACTERISTICS

LIGHT STABILITY TEST (ASTM F-1515) : CLASS 4

RESISTANCE TO CHEMICALS (ASTM F-925-24) : NO CHANGE

- (24 HOURS FOR SURFACE ATTACK, DULLING, OR COLOR CHANGE)
- CHEMICALS TESTED : ACETIC ACID (5%), ISOPROPYL ALCOHOL (70%), AMMONIA (5%), BLEACH, OLIVE OIL & OTHERS

STAINING AND COLOR TRANSFER TO ADJACENT SURFACE (ASTM F 1861-02): NONE

FIRE - SINGLE-FLAME SOURCE TEST (ISO 11925): PASS

FIRE - TUNNEL TEST (ASTM E-84) : CLASS C

STATIC LOAD LIMIT (ASTM F-970) (100 LBS PSI): .0005 INCH

GREEN FEATURES

OUR ANDELINE RECYCLED LEATHERS MAY CONTRIBUTE TO LEED® IN THESE CATEGORIES :

MR	-	4.1 / 4.2	RECYCLED CONTENT (PRE-CONSUMER)
IAC	-	4.2 / 4.3	LOW-EMISSION ADHESIVE AND PRODUCT
LOCAL	-	5.1 / 5.2	500 MILE RADIUS MANUFACTURING
RENEWABLE	-	6.0	RAPIDLY RENEWABLE RESOURCE AND MATERIAL

EcoDomo is a member of the US Green Building Council and CoopAmerica. We consider paying for carbon credits, wind-generated electricity, and recycled materials as essential as paying for rent and other utilities. Visit www.ecodomo.com for more details.