

Glass fiber Wall Covering

General Description

Glass fiber wall covering is used to cover walls and other interior surfaces. Product is perfect for new spaces: thanks to its high mechanical properties it prevents cracks from appearing, consequently prolonging the surface lifetime. It is also a performing solution for light renovation: it covers cracks and wall irregularities. Pre-painted product, it saves one layer of paint during application 1 day of drying time (paint), 20 % of working time.

Technical Characteristics

Technical Characteristics	
Composition	100 % coated glass fiber
Treated fabric weight (average value)	160 g/m ² (± 8 %)
LOI	18.6%
Emission in indoor air	A+
Oekotex certificate standard 100	Class II
Fire resistance (EN 13501-1)	Euroclass B-s1,d0
Recommendation for application	
Quantity of glue	250 g/m ² (approximate)
Quantity of acrylic paint	200-300 g/m ²
Dimensions & Packaging	
Width (individual value)	100 cm (± 1 % or closed pattern repeat)
Roll length (individual value) (1)	10.5 (± 1 %)
Paintable surface (2)	Outside
Roll packaging (2)	Plastic foil
Label on roll (2)	With installation instructions
# rolls / pallet	72
Storage conditions	Dry room, storing temperature from -10 °C to +50 °C. If product is not processed up to one week, it is not recommended to open a package or to remove a package from a roll.
Quality Control	
Traceability (2)	Lot no. marked on the backside of the roll and on the small sticker on the roll
Defects marked by label (2)	Maximum 3 point defects / 50 m roll (2)
Each defect is balanced by	Adding 50 cm / defect (2)
Product is carefully checked before leaving the factory but should also be checked just before applying. Any claim should be accompanied with roll sticker and a sample featuring the defect.	

(1) Other dimensions or features on request
 (2) Details are described in works standard 0337

Technical Data Sheet

Properties

- Tear resistant
- High tensile strength
- Fire resistant
- Easy re-paintable
- Breathable
- Prepainted



Edited by:
ADFORS Construction Products Europe

SAINT-GOBAIN ADFORS CZ s.r.o.
 Sokolovska 106
 CZ - 570 21 Litomyšl
 Tel: +420 461 651 111
 Fax: +420 461 612 769
www.adfors.com

ADFORS Construction Products Europe
 reserves the right to change the information given
 herein without prior notice.

Last update: 06/01/2016